

**NEX10X ALSO AVAILABLE**

NEX10X is the same ribbon grade but coated on 4.0 micron PET film allowing for longer ribbon lengths

# NEX10

## HIGH PERFORMANCE NEAR EDGE WAX RESIN

### PRODUCT DESCRIPTION

This high performance near edge wax resin grade is the most flexible product designed to offer excellent all-round performance on near edge technology desktop, industrial and in-line coding printer systems. This grade offers maximum print performance on all types of coated or non-coated label materials along with all types of packaging films and medical paper. It has a proven track record as a drop-in replacement for the branded products supplied by OEMs such as Toshiba TEC, Avery, Markem, Videojet & ICE. With ISEGA approval, this grade is the ideal choice for in-line coders or desktop printers used in food packaging applications. It prints at a low temperature and offers bold, black prints at print speeds of up to 20 inches per second as well as having a high resin content that allows for high levels of durability to the printed image. This grade is available in a very wide range of stock sizes for next day delivery.

### RECOMMENDED SUBSTRATES

Coated paper and tag materials, synthetic paper, polyethylene, polypropylene, polyolefin, medical paper, most types of flexible packaging films

### PERFORMANCE PROPERTIES

#### PRINT SENSITIVITY

9

#### HEAT RESISTANCE

7

#### ABRASION RESISTANCE

9

#### SOLVENT RESISTANCE

4

#### LABEL ADAPTABILITY

9

LOW

MEDIUM

HIGH

### TYPICAL APPLICATIONS



PHARMACY



SHELVING



LOGISTICS



RETAIL



GENERAL



INVENTORY



PRODUCT ID



SHIPPING



HORTICULTURE

FLEXIBLE  
PACKAGING

HEALTHCARE

ASSET  
TRACKING

# NEX10

## HIGH PERFORMANCE NEAR EDGE WAX RESIN

### PERFORMANCE CHARACTERISTICS

- Prints on most types of packaging films
- Prints on all types of coated papers and synthetic films
- Prints black, bold and crisp text, graphics and barcodes
- Excellent scratch and smudge resistance
- Excellent print quality at speeds up to 500 mm/sec
- Excellent print definition for clean, durable and dense barcodes
- ISEGA certification
- Easy slot-in product replacement for other wax resin grades

### Near Edge Technology Grades\*

<b>NEX10</b>	<b>High Performance Wax Resin</b> Very versatile for all types of labels and packaging films
<b>NEX10X</b>	<b>High Performance Wax Resin</b> Coated on 4.0-micron film for longer length ribbons
<b>NEX75</b>	<b>Specialty Wax Resin</b> For extra durability and higher print speeds
<b>UEX40</b>	<b>Specialty Resin</b> Extra durability to heat and abrasion with high print speeds

\*These ribbon grades are for use with near edge technology printers. We also offer ribbons grades for flat head technology printers and thermal transfer coders.

### RIBBON SPECIFICATIONS

DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7.0 Microns +/- 0.02
INK TYPE	Wax/Resin (near edge technology)
COLOUR	Black
INK MELTING POINT	70°C
DENSITY	1.8

### RIBBON STORAGE CONDITIONS

DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

### CERTIFICATIONS AND APPROVALS

DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



**TTS**  
Thermal Transfer Solutions Limited

A Todayt Group Company



**UK Office**

**Thermal Transfer Solutions Ltd**

Unit 27, Eagle Road

Manorside Industrial Estate

Redditch, Worcestershire, B98 9HE

**T:** +44 (0)1527 517577 | **F:** +44 (0)1527 517533

**E:** sales@tts.eu.com



**TTS**  
Thermal Transfer Solutions BV

A Todayt Group Company



**Dutch Office**

**Thermal Transfer Solutions BV**

De Factorij 4

1689 AL Zwaag

The Netherlands

**T:** +31 (0)229 859 831

**E:** eusales@tts.eu.com