

PDX20

COLOURS

PREMIUM FLAT HEAD WAX RESIN

PRODUCT DESCRIPTION

This grade is an excellent all-round premium wax resin ribbon available in a wide range of vivid colours – great for printing dark, crisp images and barcodes on a range of paper and synthetic labels. It also offers the durability and smudge/scratch resistance expected of such a premium product. Developed specifically to cover the widest possible range of pre-printed labels, it gives excellent performance on various inks used in the spot and flood coating processes, eliminating any possible slippage during the printing process. Additional thermal transfer varnish on the label is not required, thus reducing total cost of ribbon and label. It also features an excellent backcoat system which combined with the unique ink formulation dissipates static and is versatile enough to print on a wide variety of both paper and synthetic label stocks.

AVAILABLE COLOURS



RECOMMENDED SUBSTRATES

Coated/uncoated paper & tag stocks, synthetic paper, polyethylene, polypropylene, polyolefin, gloss paper, flood-coated paper, UV varnished labels

PERFORMANCE PROPERTIES

PRINT SENSITIVITY




HEAT RESISTANCE



ABRASION RESISTANCE



SOLVENT RESISTANCE









LABEL ADAPTABILITY



LOW MEDIUM HIGH

TYPICAL APPLICATIONS

 PHARMACY	 SHELVING	 LOGISTICS	 RETAIL
 GENERAL	 INVENTORY	 PRODUCT ID	 RFID
 HORTICULTURE	 NUMBER PLATES	 SHIPPING	 SIGNAGE



PDX20

COLOURS

PREMIUM FLAT HEAD WAX RESIN

PERFORMANCE CHARACTERISTICS

- Ideal for printing on spot and flood coated labels
- Prints on a wide variety of substrates from uncoated papers to mid-range synthetic films
- Dark, dense images for reliable printing
- Prints at high speeds (12 IPS)
- Dissipates static
- Good smudge and scratch resistance
- Features enhanced printer performance

Flat Head Technology Grades*

EWX10
COLOURS

Premium Wax

Best choice for general purpose labelling

PDX20
COLOURS

Premium Wax Resin

General purpose labelling with extra durability

PDX60
COLOURS

High Performance Wax Resin

Great print performance with very good durability

SRX35
COLOURS

Premium Resin

Extra scratch resistance on synthetic labels

SDX80
COLOURS

Premium Textile Resin

Excellent print on textiles with wash resistance

*These ribbon grades are for use with flat head technology printers. We also offer ribbons grades for near edge technology printers and thermal transfer coders.

RIBBON SPECIFICATIONS

DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7.5 Microns +/- 0.02
INK TYPE	Wax/Resin (flat head technology)
COLOUR	Various
INK MELTING POINT	70-80°C (depending on colour)
DENSITY	Varies (according to colour)

RIBBON STORAGE CONDITIONS

DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS

DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



BS 5609
(*RED ONLY)



TTS
Thermal Transfer Solutions Limited



TTS
Thermal Transfer Solutions B.V.



UK Office

Thermal Transfer Solutions Ltd

Unit 27, Eagle Road
Manorside Industrial Estate
Redditch, Worcestershire, B98 9HE

T: +44 (0)1527 517577 | **F:** +44 (0)1527 517533

E: sales@tts.eu.com



Dutch Office

Thermal Transfer Solutions BV

Groteweg 9,
1756 CK 't Zand
The Netherlands

T: +31 (0)224 22 74 56

E: jordy.brouwer@tts.eu.com



French Speaking Office

Egaartbaan 23
B-1741 Wambeek
Belgium

T: +32 (0)473 371279

E: pva@tts.eu.com