

SDX 80

COLOURS

PREMIUM TEXTILE FLAT HEAD RESIN

PRODUCT DESCRIPTION

This premium resin grade has been specially developed to meet the requirements of the textile printing market. It is a highly durable wash care resin that provides an excellent printing quality of very small text, large characters, logos, and all types of barcodes. It is suitable for printing onto various materials such as nylon, polyester, acetate, rayon, and other synthetic fibres which are present in today's market. The printed image will have great resistance to heat, water and industry solvents allowing great durability against home or industrial washing, dry cleaning, bleach washing and ironing - up to 150°C. It is also manufactured with outstanding back coat technology which will ensure excellent printhead protection, allow no clogging and prevent static build up.

AVAILABLE COLOURS



RECOMMENDED SUBSTRATES

Nylon, Polyester, Acetate, Rayon, Polyethylene, Polypropylene, PVC, PET, Vellum, matt and gloss-coated paper, cast-coated paper like Chromolux, Cardboard materials, PE, PP, PS, and other synthetic films

PERFORMANCE PROPERTIES

PRINT SENSITIVITY



HEAT RESISTANCE



ABRASION RESISTANCE



SOLVENT RESISTANCE








LABEL ADAPTABILITY



LOW MEDIUM HIGH

TYPICAL APPLICATIONS

- 
CARE LABELS
- 
TEXTILE
- 
DRY CLEANING
- 
AUTOMOTIVE
- 
AVIATION



SDX80

COLOURS

PREMIUM TEXTILE FLAT HEAD RESIN

PERFORMANCE CHARACTERISTICS

- Offers excellent print quality on textile materials
- High scratch and smear resistance to washing, drying and ironing
- Withstands extreme heat
- Steam resistant
- Specially formulated backcoating for printhead protection
- Excellent white print density on dark textile materials

Flat Head Technology Grades*

EWX10 COLOURS	Premium Wax Best choice for general purpose labelling
PDX20 COLOURS	Premium Wax Resin General purpose labelling with extra durability
PDX60 COLOURS	High Performance Wax Resin Great print performance with very good durability
SRX35 COLOURS	Premium Resin Extra scratch resistance on synthetic labels
SDX80 COLOURS	Premium Textile Resin Excellent print on textiles with wash resistance

*These ribbon grades are for use with flat head technology printers. We also offer ribbons grades for near edge technology printers and thermal transfer coders.

RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7 Microns +/- 0.02
INK TYPE	Resin (flat head technology)
COLOUR	Various
INK MELTING POINT	85°C
DENSITY	Varies (according to colour)

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS	
DESCRIPTION	TECHNICAL
SO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SCHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



UK Office
Thermal Transfer Solutions Ltd
 Unit 27, Eagle Road
 Manorside Industrial Estate
 Redditch, Worcestershire, B98 9HE
T: +44 (0)1527 517577 | **F:** +44 (0)1527 517533
E: sales@tts.eu.com

Dutch Office
Thermal Transfer Solutions BV
 Groteweg 9,
 1756 CK 't Zand
 The Netherlands
T: +31 (0)224 22 74 56
E: jordy.brouwer@tts.eu.com

French Speaking Office
 Egaartbaan 23
 B-1741 Wambeek
 Belgium
T: +32 (0)473 371279
E: pva@tts.eu.com