

ADVANTAGE range

TDM227X

HIGH PERFORMANCE NEAR EDGE WAX RESIN

THIS GRADE IS THE SAME AS TDM227

But coated on 4.0 micron PET film allowing for longer ribbon lengths

PRODUCT DESCRIPTION

This high performance near edge wax resin grade is the most flexible product designed to offer excellent all-round performance on near edge technology desktop, industrial and in-line coding printer systems. This grade offers maximum print performance on all types of coated or non-coated label materials along with all types of packaging films and medical paper. It has a proven track record as a drop-in replacement for the branded products supplied by OEMs such as Toshiba TEC, Avery, Markem, Videojet & ICE. With ISEGA approval, this grade is the ideal choice for in-line coders or desktop printers used in food packaging applications. It prints at a low temperature and offers bold, black prints at print speeds of up to 20 inches per second as well as having a high resin content that allows for high levels of durability to the printed image. This grade is available in a very wide range of stock sizes for next day delivery.

RECOMMENDED SUBSTRATES

Coated paper and tag materials, synthetic paper, polyethylene, polypropylene, polyolefin, medical paper, most types of flexible packaging films

PERFORMANCE PROPERTIES

PRINT SENSITIVITY

9

HEAT RESISTANCE

7

ABRASION RESISTANCE

9

SOLVENT RESISTANCE

4

LABEL ADAPTABILITY

9

LOW

MEDIUM

HIGH

TYPICAL APPLICATIONS



PHARMACY



SHELVING



LOGISTICS



RETAIL



GENERAL



INVENTORY



PRODUCT ID



SHIPPING



HORTICULTURE



FLEXIBLE
PACKAGING



HEALTHCARE



ASSET
TRACKING



TDM227X

HIGH PERFORMANCE NEAR EDGE WAX RESIN

PERFORMANCE CHARACTERISTICS

- Coated on 4.0 micron PET film allowing for longer ribbon lengths
- Prints on most types of packaging films
- Prints on all types of coated papers and synthetic films
- Prints black, bold and crisp text, graphics and barcodes
- Excellent scratch and smudge resistance
- Excellent print quality at speeds up to 500 mm/sec
- Excellent print definition for clean, durable and dense barcodes
- ISEGA certification
- Easy slot-in product replacement for other wax resin grades

Near Edge Technology Grades*

TDM227	High Performance Wax Resin Very versatile for all types of labels and packaging films
TDM227X	High Performance Wax Resin Coated on 4.0-micron film for longer length ribbons
TDR540	Specialty Resin Extra durability to heat and abrasion with high print speeds

*These ribbon grades are for use with near edge technology printers. We also offer ribbons grades for flat head technology printers and thermal transfer coders.

RIBBON SPECIFICATIONS

DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.0 Micron Polyester
TOTAL RIBBON THICKNESS	6.5 Microns +/- 0.02
INK TYPE	Wax/Resin (near edge technology)
COLOUR	Black
INK MELTING POINT	68°C
DENSITY	1.8

RIBBON STORAGE CONDITIONS

DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS

DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



Todaytec Group Europe



UK Office: Unit 27 Eagle Road, Manorside Industrial Estate, Redditch.
Tel; +44 (0)1527 517577 Email; sales@tts.eu.com

BV Office: De Factorij 4, 1689 AL Zwaag, The Netherlands
Tel; +31 (0)229 859831 Email; eusales@tts.eu.com

German Office: Arnold-Sommerfeld-Ring 13, 52499 Baesweiler,
Tel; +49 (0)2401 9179 0 | Email; info@calor.de

French Office: 6 Rue Verdier Monetti, 76880 Arques la Bataille,
Tel; +33 (0)235048665 Email; info@regmatt.com